

20' CONTAINER OPEN SIDE

CORTEN STEEL & WOOD FLOOR



External	length width height	6.058 mm 2.438 mm 2.591 mm
Internal	length width height	5.898 mm 2.288 mm 2.328 mm
Door opening	width height	2.340 mm 2.278 mm
Side Door opening	width height	5.642 mm 2.278 mm
Max gross weight Payload Tare weight		24.000 kg 20.580 kg 3.420 kg
Cubic capacity		30,4 m ³ /1,074 cu.ft
Fork Pocket	width height centre distance	360 mm 118 mm 2,050 mm
Handling devices	Top and bottom corner castings in ISO 20' position	
Stacking	Stacking 192.000 kg.	
Floor strength	5.460 kg axle loading	
Main materials	Corten A, floor 28 mm plywood	

All measurements are approx.

containertech as

Gramveien 16, 1832 Askim, Norway
 Tel: +476988 7970 - Telefax +47 6988 7979
 www.containertech.no - e-mail: post@containertech.no

ADVANTAGES

- Full Side access
- Galvanized locking bars.
- Cut outs, reduced stacking damages

STANDARDS

Container complies with following standards and their latest editions:
ISO/TC-104



- 668 Series 1 freight containers-Classification, external dimensions and ratings
- 6346 Coding, identification and marking for freight containers
- 1161 Specification of corner fittings for series 1 freight containers
- 1496/1 Specification and testing of series 1 freight containers
Part 1 : General cargo containers for general purposes
- 830 Freight containers-Terminology

The International Union of Railway (UIC) code 592-2 OR.

The Customs Convention on the International Transport of Goods (TIR).

The International Convention for Safe Containers (CSC).